



LSP 3040

SPECIFICATIONS

DESCRIPTION

MODEL - LSP 3040

GVWR - 20,000 lbs.

Over All Length - approx.. 35 ft.

Over All Width - 102 in.

Stick Pipe Capacity - 40 ft.

Empty Weight - 6,200 lbs.

RUNNING GEAR

Axle - 10,000 lbs.

Brakes - Electric

Tires - 235/75R17.5 Load Range (J) 128 psi

Wheels - 17.5 x 6.75 8 Bolt White Mod (P)

Suspension - Slipper leaf spring

FRAME

Main Frame - 10 in. Channel

Outer Extensions - 7 in. Square tube

Inner Extensions - 6 in. Square tube

A Frame Tongue - 6 in. Channel

Bumper - 4 x 10 in. Rectangular tube

Fenders - 10 GA. Formed Channel

Headache Rack - 24 in. x 102 in.

Braces - 1 1/2 in. Square tube

ELECTRICAL

Plug - 7 RV molded plug

Wiring - Enclosed in conduit w/ junction boxes
- connections soldered & shrink wrapped

Lights - Standard LED package

SAFETY

Chains - Rated to match

Break Away - Battery, battery box, and switch

Decals - Warning decals & reflective tape

ACCESSORIES

Roller System - 8) 10 in. Rubber rollers

Jacks - Dual 12K spring loaded drop leg

FINISH

PPG Paint - Industrial urethane- White, Black, Orange, Yel.

BOLSTERS

Material - 3 x 5 in. Rectangular tubes

Stakes - 1 1/2 in. Cold Rolled Round

Plastic Liner - 2 1/2 in. UHMW plastic strips

Tiedowns - 4 in. x 27 ft. tie down straps

